

HG 2620 E

NEW!

Available October 2016

Technical Specifications

Voltage: 120 VAC / 60Hz
Output: 1750 watts
Amps: 14.6
Temperature: 120 – 1300 °F (50 – 700 °C) (continuously variable)
Airflow rate: 2 – 13 cfm. (continuously variable)
Air pressure: 3,000 Pa
Highlights: Restart protection, LCD display always in view, 4 settings programmable, locable override funktion (LOC), single-hand operation by toggle, magnesium guard sleeve, plug-in heating element, residual heat indicator, fine dust filter, construction use, easily replaceable power cord, ergonomic soft grip handle, optional temperature scanner

Power cord: Industrial grade rubber
Motor: Brushless motor
Heating element: Ceramic heating element
Motor lifetime: Approx. 10,000 hrs.
Heater lifetime: Approx. 800 hrs.
Accessories: Use of our professional accessories

Dimensions: 14.10" x 3.60" x 3.70" (l x w x h)
Net Weight: 1.85 lbs (29.63oz)
Single Sell Pack Box : Dimensions: 17.13" x 4.13" x 4.13"
 Weight: 3.26 lbs (52.10 oz)

Single Sell Pack Case: Dimensions: 15.35" x 4.33" x 12.6"
 Weight: 5.17 lbs (82.65 oz)

Country of origin: Romania
Warranty: One year limited



| UPC-Code | Prod. No. | Version |
|--------------|-----------|---------|
| 018139376002 | 110025600 | Box |
| 018139376019 | 110047485 | Case |



RoHS
Compliant



double insulated

ISO
9001:
2015
14001:
2015